

MeasureEffect™

PVM-1530



IRM-1



CMP-1015-PV



PVM-1530
reSYNC
automatic
synchronization of
STC parameters

Professional meter for photovoltaic installations up to 1500 V

Features

PVM-1530

- It can be used for category 1 measurements according to EN 62446-1.
- It allows the measurement of the I-U curve for category 2 according to EN 62446-1 and EN 61829.
- It allows the measurement of photovoltaic panels, including bifacial and high-efficiency panels.
- Ability to define measurement procedures.
- It converts measured parameters into STC conditions according to EN IEC 60891 by cooperation with the IRM-1 solar radiation and temperature meter.
- reSYNC function – automatic completion of results with environmental parameters and their conversion to STC conditions after restoring connection with IRM-1.
- The attachable radio interface ensures cooperation with the IRM-1 meter over long distances.
- Built-in Bluetooth and Wi-Fi for communication with external devices.
- Large structured memory of measurements.
- Large touchscreen for good visibility in bright sunlight.

IRM-1

- Measurement of solar radiation and temperature.
- The LoRa interface for communication with a master meter – offers a larger range than the Bluetooth technology!
- Automatic data synchronization with a master meter with reSYNC function.
- Built-in compass and inclination sensor.
- Built-in recorder that can be used to record solar radiation before constructing PV systems, as well as to measure the shading of existing systems.
- Large measurement memory: 999 cache memory cells and 5000 recorder records available (one-time recording) with the option of overwriting them (continuous recording).

Choose the best set for your needs

PVM-1530

IRM-1

CMP-1015-PV

PVM-1530 Max

Photovoltaic meter, two solar radiation and temperature meters and clamp meter



PVM-1530 Pro

Photovoltaic meter, solar radiation and temperature meter and clamp meter



PVM-1530

Photovoltaic meter



Sonel MeasureEffect™

The meter is a part of the **Sonel MeasureEffect™** platform. It is a comprehensive system that enables you to take measurements, store and manage data, and provides multi-level control of your instruments.

Measured parameters

PVM-1530

- Measurement of I-U and P-U characteristics. Conversion to STC conditions.
- The open circuit voltage of the PV panel or a chain of panels, up to 1500 V DC.
- RMS voltage of the AC network up to 1000 V with frequency measurement.
- Short circuit current of a PV panel or chain of panels - up to 40 A DC.
- Insulation resistance of PV panels - measuring voltage of 250, 500, 1000, 1500 V DC, simultaneous measurement of two values: R_{ISO+} and R_{ISO-} .
- Insulation resistance of AC circuits - measuring voltage 250, 500, 1000 V DC.
- Resistance of protective conductors and equipotential bonding with ± 200 mA current.
- Measurement of PV panels operating current and AC current - all with CMP-1015-PV meter.
- AC/DC power measurement.
- Test of bypass diodes, automatic polarity detection.
- Test of blocking diodes with 1000, 1500 V DC voltage.

IRM-1

- Solar radiation intensity (irradiance) in W/m^2 or BTU/ft^2h .
- PV panel temperature in $^{\circ}C$ or $^{\circ}F$.
- Ambient temperature in $^{\circ}C$ or $^{\circ}F$.
- Inclination angle of panels
- Orientation of the panels with the built-in compass.





PVM-1530: cat. 1 measurements and I-U characteristics –

The PVM-1530 is a pioneering meter for photovoltaic installations up to 1500 V with such a substantial number of measurement functions. Their selection is done via a touch screen. The screen is large, colorful and with strong backlight so that operation in full sunlight is not a problem. Extensive structural memory significantly reduces the time for preparing post-measurement documentation.

IRM-1: simple and compact –

IRM-1, small, but indispensable for testing PV systems. By measuring solar radiation values, as well as panel and ambient temperatures, it provides the necessary data to convert the results into STC conditions. A built-in recorder with a memory of 5000 records enables the instrument to be used as a tool in the PV plant design process, as well as to diagnose panel shading problems.

Tightness and durability –

The meters perform well in harsh environmental conditions. The PVM-1530's housing is rugged and tight when closed to easily ensure that the meter is protected during measurement.



Communication and software –

Measurement data from the IRM-1 can be transferred to a computer via the USB port. In addition, the device has a built-in wireless **LoRa interface** (Long Range) for automatic data exchange with the master meter – even over long distances.

Measurement data from the PVM-1530 can be transferred to a computer via cable or wireless communication. Saving the downloaded data to popular formats and printing is ensured by **Sonel Reader**. In order to generate a report on electric shock protection use the optional software: **Sonel Reports Plus**.

Trouble? reSYNC! –

It may happen that in the course of measurements the PVM-1530 moves away from the IRM-1 so far, that communication between them is lost. If the measurements are continued, then after the connection is restored, the results will be automatically **supplemented with environmental parameters**, which in the meantime were recorded by the IRM-1 in its **temporary memory**, and converted into STC conditions.



Specifications

| Parameter | Measurement range | Display range | Resolution | Accuracy $\pm(\% \text{ m.v.} + \text{digits})$ |
|---|---|------------------------------------|---------------------|--|
| Voltage | | | | |
| AC voltage | 0.0 V...1000.0 V | 0.0 V...1000.0 V | 0.1 V | $\pm(2\% \text{ m.v.} + 6 \text{ digits})$ |
| DC voltage | 0.0 V...1500.0 V | 0.0 V...1500.0 V | 0.1 V | $\pm(0.5\% \text{ m.v.} + 2 \text{ digits})$ |
| Frequency | 10.0 Hz...100.0 Hz | 0 Hz...100.0 Hz | 0.1 Hz | $\pm(0.5\% \text{ m.v.} + 2 \text{ digits})$ |
| Short circuit current I_{sc} | | | | |
| Voltage 1500 V DC | 0.00...30.00 A | 0.00...30.00 A | 0.01 A | $\pm(1\% \text{ m.v.} + 2 \text{ digits})$ |
| Voltage 1000 V DC | 0.00...40.00 A | 0.00...40.00 A | 0.01 A | $\pm(1\% \text{ m.v.} + 2 \text{ digits})$ |
| Insulation resistance | | | | |
| Insulation resistance at AC side | | | | |
| Measuring voltage 250 V | 250 k Ω ...200 M Ω acc. to EN IEC 61557-2 | 0.0 k Ω ...200.0 M Ω | from 0.1 k Ω | $\pm(3\% \text{ m.v.} + 8 \text{ digits})$ |
| Measuring voltage 500 V | 500 k Ω ...500 M Ω acc. to EN IEC 61557-2 | 0.0 k Ω ...500.0 M Ω | from 0.1 k Ω | $\pm(3\% \text{ m.v.} + 8 \text{ digits})$ |
| Measuring voltage 1000 V | 1000 k Ω ...1.000 G Ω acc. to EN IEC 61557-2 | 0.0 k Ω ...1.000 G Ω | from 0.1 k Ω | $\pm(3\% \text{ m.v.} + 8 \text{ digits})$ |
| Insulation resistance at DC side | | | | |
| Measuring voltage 250 V / 500 V / 1000 V / 1500 V | 250 k Ω ...500 M Ω acc. to EN IEC 61557-2 | 0.0 k Ω ...500.0 M Ω | from 0.1 k Ω | $\pm(8\% \text{ m.v.} + 8 \text{ digits})$ |
| Resistance of protective conductors and equipotential bondings | | | | |
| Measurement of resistance of protective conductors and equipotential bondings with ± 200 mA current | 0.10 Ω ...1999 Ω acc. to EN IEC 61557-4 | 0.00 Ω ...1999 Ω | from 0.01 Ω | from $\pm(2\% \text{ m.v.} + 3 \text{ digits})$ |
| Operating current | as for CMP-1015-PV | as for CMP-1015-PV | as for CMP-1015-PV | as for CMP-1015-PV |
| Active power | 0.0 kW...999.0 kW | 0.0 kW...999.0 kW | 0.1 kW | $\pm(6\% \text{ m.v.} + 5 \text{ digits})$ |

Other technical data

Safety and work conditions

Measuring category according to EN IEC 61010-2-030

| | |
|---|-------------------|
| Terminal group: „-“, „+“, \perp | CAT III 1500 V DC |
| Terminal group: R_{CONT-} , R_{CONT+} | CAT III 600 V |

Ingress protection

| | |
|--------------|------|
| Closed cover | IP65 |
| Open cover | IP40 |

Type of insulation according to EN 61010-1 and EN IEC 61557

| | |
|--|--------|
| | double |
|--|--------|

| | |
|---------------------|--|
| Power supply | mains, Li-Ion 7.2 V, 9.8 Ah rechargeable battery |
|---------------------|--|

| | |
|-------------------|--------------------|
| Dimensions | 390 x 308 x 172 mm |
|-------------------|--------------------|

| | |
|---------------|------------|
| Weight | ca. 8.8 kg |
|---------------|------------|

| | |
|------------------------------|-------------|
| Operating temperature | -10...+45°C |
|------------------------------|-------------|

| | |
|----------------------------|-------------|
| Storage temperature | -20...+60°C |
|----------------------------|-------------|

| | |
|-----------------|----------|
| Humidity | 20...90% |
|-----------------|----------|

| | |
|----------------------------|--------------|
| Nominal temperature | 23 \pm 2°C |
|----------------------------|--------------|

| | |
|---------------------------|-----------|
| Reference humidity | 40%...60% |
|---------------------------|-----------|

Memory and communication

| | |
|--------------------------------------|--------------|
| Memory of measurement results | 9999 records |
|--------------------------------------|--------------|

















| | |
|--------------------------|------------------------------|
| Data transmission | USB, RJ-45, Bluetooth, Wi-Fi |
|--------------------------|------------------------------|

| | |
|---------------------------------|----------|
| Communication with IRM-1 | wireless |
|---------------------------------|----------|






Other information

| | |
|--|------------------------------------|
| The product meets the EMC (emission for industrial environment) requirements according to standards | EN IEC 61326-1 EN IEC 61326-2-2 |
|--|------------------------------------|

Standard accessories















| | | PVM-1530 Max | PVM-1530 Pro | PVM-1530 |
|---|--|----------------|----------------|-------------|
| | | WMGBPVM1530MAX | WMGBPVM1530PRO | WMGBPVM1530 |
|  | IRM-1 solar radiation and temperature meter WMGBIRM1 | 2 | 1 | |
|  | CMP-1015-PV digital clamp meter for photovoltaic installations + standard accessories WMGBCMP1015PV | 1 | 1 | |
|  | LORA-S1 USB adapter for data transmission WAADAUSBLORA | 1 | 1 | |
|  | MC4-banana sockets adapter 1.5 kV (set) WAADA5KVMC4KPL | 1 | 1 | 1 |
|  | Cable 2 m with MC4 plugs (set of 2 pcs) WAPRZ002MC4KPL | 1 | 1 | 1 |
|  | Test lead 3 m blue 5 kV (banana plugs) WAPRZ003BUBB5K | 1 | 1 | 1 |
|  | Test lead 3 m yellow CAT III 1500 V (banana plugs) WAPRZ003YEBB1K5V | 1 | 1 | 1 |
|  | Test lead 1.8 m red 5 kV (banana plugs) WAPRZ1X8BLBB5K | 1 | 1 | 1 |
|  | Test lead 1.8 m black 5 kV (banana plugs) WAPRZ1X8BLBB5K | 1 | 1 | 1 |
|  | Crocodile clip 1 kV 20 A black WAKROBL20K01 | 2 | 2 | 2 |
|  | Pin probe 5 kV (banana socket) black WASONBLOGB2 | 2 | 2 | 2 |
|  | Solar radiation meter mounting kit for PV panels + probe for measuring the temperature of PV panels and the ambient temperature WASONTPVCKPL | 2 | 1 | |
|  | 5 V power supply with USB 2.0 output and a detachable micro-USB cable WAZASZ24 | 2 | 1 | |
|  | L-4 carrying case WAFUTL4 | 1 | 1 | 1 |
|  | USB cable WAPRZUSB | 1 | 1 | 1 |
|  | Mains cable with IEC C13 plug WAPRZ1X8BLIEC | 1 | 1 | 1 |









Standard accessories

| | PVM-1530 Max | PVM-1530 Pro | PVM-1530 |
|--|----------------|----------------|-------------|
| | WMGBPVM1530MAX | WMGBPVM1530PRO | WMGBPVM1530 |
|  Key for MC4 connectors WAPOZKEYMC4 | 1 | 1 | 1 |
|  Fuse 0.5 A, 1000 V AC/DC, 6.3x32 mm WAPOZB05A1000V | 1 | 1 | 1 |
|  Factory calibration certificate - PVM-1530 | 1 | 1 | 1 |
|  Factory calibration certificate - IRM-1 | 2 | 1 | |
|  Factory calibration certificate - CMP-1015-PV | 1 | 1 | |



Optional accessories

| | PVM-1530 Max | PVM-1530 Pro | PVM-1530 |
|---|----------------|----------------|-------------|
| | WMGBPVM1530MAX | WMGBPVM1530PRO | WMGBPVM1530 |
|  IRM-1 solar radiation and temperature meter WMGBIRM1 | | ✓ | ✓ |
|  CMP-1015-PV digital clamp meter for photovoltaic installations + standard accessories WMGBCMP1015PV | | | ✓ |
|  Optional accessories for CMP-1015-PV | ✓ | ✓ | |
|  MC4 splitter for power measurement in PV installations 1500 V (set of 2 pcs.) WAADAMC4SV2KPL | ✓ | ✓ | ✓ |
|  AC-16 line splitter (facilitates current measurements) WAADAAC16 | ✓ | ✓ | ✓ |
|  Industrial socket adapter 16 A / 32 A WAADAAGT16T / WAADAAGT32T | ✓ | ✓ | ✓ |
|  Three-phase socket adapter 16 A / 32 A WAADAAGT16P / WAADAAGT32P | ✓ | ✓ | ✓ |
|  Three-phase socket adapter 63 A WAADAAGT63P | ✓ | ✓ | ✓ |
|  Crocodile 1 kV 20 A clip red / blue / yellow WAKRORE20K02 / WAKROBU20K02 / WAKROYE20K02 | ✓ | ✓ | ✓ |
|  Pin probe 1 kV (banana socket) red / blue / yellow / black WASONREOGB1 / WASONBUOGB1 / WASONYEGB1 / WASONBLOGB1 | ✓ | ✓ | ✓ |
|  Barcode scanner (USB) WAADACK2D | ✓ | ✓ | ✓ |
|  Report / barcode printer D2 SATO (USB, portable) WAADAD2 | ✓ | ✓ | ✓ |
|  Tape / paper (glued) for D2 printer WANAKD2 | ✓ | ✓ | ✓ |
|  Ink tape for D2 printer WANAKD2BAR | ✓ | ✓ | ✓ |

| | | PVM-1530 Max | PVM-1530 Pro | PVM-1530 |
|---|---|----------------|----------------|-------------|
| | | WMGBPVM1530MAX | WMGBPVM1530PRO | WMGBPVM1530 |
|  | Report / barcode printer D3 Brother (Wi-Fi / USB, portable) WAADAD3 | ✓ | ✓ | ✓ |
|  | Ink tape for D3 printer WANAKD3 | ✓ | ✓ | ✓ |
|  | Rechargeable battery for D3 printer WAAKU19 | ✓ | ✓ | ✓ |
|  | Sonel Reader software WAPROREADER | ✓ | ✓ | ✓ |
|  | Sonel Reports Plus software WAPROREPORTSPUS | ✓ | ✓ | ✓ |
|  | Calibration certificate with accreditation - PVM-1530 | ✓ | ✓ | ✓ |
|  | Calibration certificate without accreditation - IRM-1 | ✓ | ✓ | |
|  | Calibration certificate with accreditation - CMP-1015-PV | ✓ | ✓ | |

